



NOVOTEST

Dew Point Meter NOVOTEST KTR-1



Dew Point Meter NOVOTEST KTR-1 is designed for rapid non-destructive control of temperature and humidity, dew point calculation and measurement temperature of surface by contact method.

Advantages of the Dew Point Meter NOVOTEST KTR-1:

- High accuracy of the analysis parameters of the environment before painting works;
- Minimum number of controls: one button - one function
- Digital contrast display
- Built-in sensors of temperature and humidity
- Built-in contact sensor for measuring the temperature of surface
- For usability, device equipped with the alarm sound while reducing the temperature difference between surface and dew point below 3 ° C
- Default settings of the device allow to operate without additional calibration
- Durable two-buttons membrane keypad
- Auto-OFF function for longer operation without battery recharging

Specifications of the Dew Point Meter NOVOTEST KTR-1

Dew Point Meter NOVOTEST KTR-1 measures:

- air temperature (-20 to + 125 ° C)
- surface temperature (-20 to + 125 ° C)
- relative humidity

and calculates:

- dew point
- difference between the dew point and temperature of surface



Available options of the Dew Point Meter NOVOTEST KTR-1

- Charger

Standard set of the Dew Point Meter NOVOTEST KTR-1

- Unit
- Charger
- Manual
- Case